


CUBE Garage Door Opener

TECHNICAL SPECIFICATION

CB 700

CB 1100

CB 1500

CB Remote

CB Rail


GENERAL

Input votage	220-240V,50-60 Hz/ 110-127V,50-60Hz		
Max.pull force	700 N	1100 N	1500 N
Max.door area	7 m ²	12 m ²	18 m ²
Max.opening speed	160mm/ second		
Bottom base material	Metal		
Installation style	Horizontal / Vertical		
Drive mechanism	Chain/ Belt		
Lighting	L.E.D		
Limit setting	Electronic		
Transformer	Overload protection		
Safety outside fuse	Including		
Smart Wifi technology	Optional		
Wireless sensor technology	Optional		

FEATURES

Soft-start / stop	Opening lifting force adjustment
Maintenance alarm	More information display
Reset factory setting	Terminal devices supported
Obstruction force setting	Photo cell on / off setting
Electronic travel limit setting	Transformer overload protection

RADIO SYSTEM

Radio technology	Rolling code
Frequency	433Mhz/ 868Mhz
Memory registers	50 codes
Transmitter	4 channels

DOOR TYPE

Sectional doors		Yes	
Tilt doors		Yes	
Max door weight	80 kg	120 kg	160 kg
Max door height	2400-5000mm		
Min headroom	30 mm		

C RAIL OPTIONS

"Pre-assembly"1piece	
2 pieces rail kit	3000mm(standard)/ 3300mm/ 3500mm/ 3800mm/ 4000mm
3 pieces rail kit	

T RAIL OPTIONS

"Pre-assembly"1piece	
3 pieces rail kit	3000mm(standard)/ 3300mm/ 3500mm/ 3800mm/ 4000mm

CERTIFICATION & WARRANTY

Certification	CE-RED, ISO9000
Motor warranty	5 Years
General warranty	3 Years

CubeTech Automation Co.,Ltd

WuXi Laantin International Building,69 Dongting Middle Road, Xishan District, Wuxi, Jiangsu, China

Tel:(0086)159 515 05 928

Email:info@cubemotor.com

Website:www.cubemotor.com

EN 12453 EN 12455